

NEW

UltraVu® II 150

THERE'S A WORLD OF OPPORTUNITY OUT THERE.

VUTEK it.

And profit.



- banners and signage
- point-of-purchase advertising
- vehicle graphics
- exhibition graphics
- posters
- display graphics
- backlit displays
- long-term outdoor graphics
- wall murals
- stage graphics

The speed, quality and reliability of VUTEK's superwide format printers is now available in an affordable, industrial-strength 1.5-meter model. Here's your opportunity to bring wide format printing to the next level.

- An excellent alternative or replacement for outdated electrostatic printers.
- Available in four- and six-color models with image quality that satisfies the most demanding customer requirements.
- Prints true 360 dpi quality output on hundreds of uncoated materials.
- Prints on materials up to 60 inches (152 cm) wide.
- Prints high-quality output at 527 square feet (49 sqm) per hour; up to four times faster than competitive products or even multiple machines.
- Up to 80% lower ink running costs compared to alternative inkjet systems.
- The perfect choice for production environments that put an emphasis on fast turnaround and superior image quality.

We provide the industry's best service and support:

- Factory training
- 24/7 technical support
- Applications assistance
- Marketing tools



VUTEK®
A DIVISION OF **efi**

UltraVu® II 150 Product Specifications

Printing Technology:

- Piezo drop-on-demand solvent inkjet technology
- 720 dpi apparent resolution (360 dpi addressable)
- One-year printer warranty (includes piezo inkjet heads, which are not considered to be consumables with VUTEK printers)
- Extended ink-system warranty available using VUTEK inks
- Low maintenance, industrial-strength printheads
- 24/7 technical support

Media/Handling:

- Size: rolls with 60" (152 cm) maximum width, 59" (150 cm) maximum print width
- Type: vinyl, pressure-sensitive, paper, mesh and textiles

Printer Models:

- The UltraVu® II 150 can be purchased in two variations:
 - Four-color (CMYK)
 - Six-color (CMYK, light cyan, light magenta)

UltraVu® II 150 RIP:

- Excellent color reproduction to match original artwork
- Intuitive graphical user interface for easy operation and calibration
- Multi-language graphical user interface
- Gamma control over global brightness

Additional RIP Features:

- ICC color management for media versatility and color accuracy
- Multi-color support for smooth highlights to mid-tone transitions, improved color quality, and increased apparent higher resolution
- Tiling feature to simplify complex printing jobs

Formats:

- All popular desktop file formats, including PostScript®3™, EPS, TIFF, PDF, RGB/CMYK

Control Station:

- Windows® operating system
- UltraVu® II 150 operating software
- DVD Reader
- 1 GB Ethernet adapter

Environmental Considerations:

- Compressed Air: 80 psi (5.63 kg/cm) minimum, 150 psi (10.56 kg/cm) maximum
- 4 cfm (113.2 lpm) dry air only
- Ambient Room Temperature: 68° F to 85° F (20° C to 29° C)
- Humidity: 30% to 80% (non-condensing)
- Weight: 2394.0 lbs. (1085.9 kg) featuring lightweight Uni-Frame construction
- Height: 64.0" (162.5 cm)
- Width: 133.0" (337.8 cm)
- Depth: 53.5" (135.8 cm)
- Electrical: single-phase, 30 amps, 200-240 VAC, 50/60 Hz



Inks:

- VUTEK supplies ink in 3.25-liter bottles of cyan, magenta, yellow, black, light magenta and light cyan
- VUTEK inks are solvent based and carry a two-year outdoor durability warranty (extended to a five-year warranty with Aquashield)
- Avery offers a 5-year Fleet ICS warranty with VUTEK inks.
- 3M offers a 5-year MSC™ with VUTEK inks.

Productivity:

Print output speed in square feet/square meters per hour:

Model

Mode/Speed

UltraVu® II 150 FC

(4 Color)
@ 59" width (150 cm)

Enhanced/Max
Ultra/Max

527/49
271/25

UltraVu® II 150 SC

(6 Color)
@ 59" width (150 cm)

Enhanced/Max
Ultra/Max

527/49
271/25

All trademarks used herein are the property of VUTEK Inc. or other companies. Windows® is a registered trademark of Microsoft Corporation. PostScript® is a registered trademark of Adobe Corporation. MSC™ is a trademark of 3M. Product specifications are subject to change without notice.

©2006 VUTEK Inc. Printed in U.S.A.



UltraVu® II 150



UltraVu® 260 SC



UltraVu® II 3360



UltraVu® II 5330



FabriVu® 3360



PressVu® UV 180 Series



PressVu® UV 200 Series



PressVu® UV 320/400



VUTEK

Headquarters & Manufacturing

One VUTEK Place
Meredith, NH 03253 USA
T. 603-279-4635
USA Toll Free 1-866-468-8835
F. 603-279-6411
e-mail: sales@vutek.com www.vutek.com

VUTEK Belgium BVBA

Sales & Support Center

Ikaros Business Park
Ikaroslaan 20
B-1930 Zaventem
Belgium
T. +32-2-749-9420
F. +32-2-749-9465